



- Weldable stud range 4 – 12 mm
- Ideal for KÖCO stud welding equipment ELTOP 502 and 802 and INVERTER 905i
- Robust housing
- Suitable for welding on building site

Technical data		Description
Stud welding with ceramic ferrule Weldable stud range ø (mm)	4 - 12	The model SK14 is a robust stud welding gun, designed for welding of threaded studs with ceramic ferrules ø 4 - 12 mm
Short cycle stud welding Weldable stud range ø (mm)	3 - 12	Ideal for short cycle stud welding ø 3 - 12 mm
Stud welding with shielding gas Weldable stud range ø (mm)	3 - 12	Best for stud welding using shielding gas ø 3 - 12 mm
Standard support with ... legs	2	Lifting range 1 - 4,5 mm
Lifting range from ... to ... (mm)	1 - 4,5	Supported by 2 legs
Input voltage lifting coil (V=)	60 - 90	
Welding cable (m/mm <sup>2</sup> )	5/35	High repeatability
Welding cable plug (mm <sup>2</sup> )	35	
Control cable (m/mm <sup>2</sup> )	5/4 x 1,0	Body made of fibre-glass reinforced polyamide
Length (excluding chuck) (mm)	185	Control cable plug (4 wire)
Body ø approx. (mm)	50	
Height (including handle) (mm)	150	
Weight excluding cables app. (kg)	0,9	