



- Weldable stud range 13 – 25 mm
- Suitable for KÖCO stud welding equipment ELOTOP 3002
- Adjustable plunge damper
- Robust housing
- Suitable for welding on building site

### Technical data

Stud welding with ceramic ferrule Weldable stud range $\varnothing$ (mm)	13 - 25
Compensation for stud length variations up to ... (mm)	8
Standard support with ... legs	3
Lifting range from ... to ... (mm)	2,5 - 6
Input voltage lifting coil (V=)	60 - 90
Lifting range from ... to ... (mm)	2,5 - 6
Welding cable (m/mm <sup>2</sup> )	2/120
Welding cable plug (mm <sup>2</sup> )	120
Control cable (m/mm <sup>2</sup> )	2/4 x 1,0
Length (excluding chuck) (mm)	300
Body $\varnothing$ approx. (mm)	63
Height (including handle) (mm)	240
Weight excluding cables app. (kg)	2,6

### Description

The model K 26 is a robust stud welding gun, especially for studs  $\varnothing$  22 – 25 mm

Suitable for das Verschweissen von Kopfbolzen SD 25 mm

Ideal for through-deck-welding TD

Most suitable for long shear studs

Compensation for stud length variations up to 8 mm

Adjustable hydraulic plunge damper

Standard support with 3 legs

Body: fibre-glass reinforced polyamide

Adjustable hydraulic plunge damper for studs from app.  $\varnothing$  14 mm

Lifting ring system with length compensation

Control cable plug (4 wire)